

05/04/99

JC598 U.S. PTO  
DAVID  
LITTENBERG  
KRUMHOLZ  
WILLIAM L. MENTLIK  
JOHN R. NELSON  
ROY H. WEPNER  
STEPHEN B. GOLDMAN  
CHARLES P. KENNEDY  
PAUL H. KOCHANSKI  
MARCUS J. MILLET  
BRUCE H. SALES  
ARNOLD B. DOMPIERI  
KEITH E. GILMAN  
ROBERT B. COHEN  
MICHAEL H. TESCHNER  
GREGORY S. GEWIRTZ  
JONATHAN A. DAVID  
SHAWN P. FOLEY\*

LAW OFFICES

LERNER, DAVID, LITTENBERG, KRUMHOLZ & MENTLIK, LLP

600 SOUTH AVENUE WEST  
WESTFIELD, NEW JERSEY 07090-1497

(908) 654-5000

FAX: (908) 654-7866

PATENTS, TRADEMARKS AND COPYRIGHTS

May 4, 1999

JOHN P. MALDJIAN  
THOMAS M. PALISI  
STEPHEN F. ROTH  
KIMBERLY V. FLUGGER  
JASON I. GARRELL  
RENEE M. ROBESON  
BRIAN K. JOHNSON  
LYNNE A. BORCHERS  
PETER A. CICALA

OF COUNSEL  
LAWRENCE I. LERNER  
DANIEL H. BOBIS

\*NORTH CAROLINA BAR ONLY  
\*NEW YORK BAR ONLY

JC542 U.S. PTO  
09/304976  
05/04/99

BOX PATENT APPLICATION  
Assistant Commissioner For Patents  
Washington, D.C. 20231

File No.: SILVERLINE 3.0-003  
Title: BLOW-OUT PREVENTION MECHANISM  
FOR WINDOWS

Inventor(s): Arthur Silverman  
Assignee: Silver Line Building Products Corporation

Dear Sir:

Enclosed herewith please find the following documents in the above-identified application for Letters Patent of the United States:

1	Pages of Abstract	Declaration
		One (1) return-addressed postcard
10	Pages of Specification	<u>PLEASE PROVIDE FILING DATE AND SERIAL NUMBER</u>
25	Number of Claims	
4	Sheets of Drawings <input checked="" type="checkbox"/> A4 <input type="checkbox"/> 11"	
X	Assignment and Recordation Form Cover Sheet	

Please charge Deposit Account No. 12-1095 in the amount of \$850.00, calculated as follows:

Basic Fee		\$ 760.00
Additional Fees:		
Total number of claims (including multiple dependent claims):	25	
Total number of claims in excess of 20:	5 x \$18	90.
Number of independent claims:	3	
Number of independent claims minus 3:	0 x \$78	0
Fee for multiple dependent claim(s) (\$260)		0
TOTAL FILING FEE		\$ 850.00

CONVENTION DATE: for Appln. S.N. is claimed.  
Priority Document: ☐ Enclosed ☐ Will follow

In the event the actual fee is greater than the payment authorized above, the Patent Office is authorized to charge any deficiency to our Deposit Account No. 12-1095.

Respectfully submitted,

LERNER, DAVID, LITTENBERG,  
KRUMHOLZ & MENTLIK, LLP

ROBERT B. COHEN

Reg. No. 32,768

LB (LBEXPC) 98020

EL096064420US

EXPRESS MAIL LABEL NUMBER:

**BLOW-OUT PREVENTION MECHANISM FOR WINDOWS****FIELD OF THE INVENTION**

The present invention relates to windows, and more particularly to windows having a feature preventing them from blowing outward during extreme storms.

**BACKGROUND OF THE INVENTION**

Exterior windows mounted in the walls of a commercial or residential building are typically provided to maintain a weather tight barrier against wind and rain. Windows also allow for a view of the exterior and the transmission of light, and preferably have the capability of being opened for ventilation during favorable conditions. If the window does not form an effective weather barrier, there may be damage to the building and/or harm to the occupants during foul weather. In extreme storm conditions, there is the potential for significant damage to the building from poorly sealed windows. Such damage may occur during hurricanes, tornadoes, or particularly severe thunderstorms. For example, in south Florida and along the Gulf Coast, hurricanes occur regularly.

In a strong storm, an exterior window may be subject to winds in excess of 100 mph (160 kph). Wind loading can be sustained, e.g., continuing for significant periods of time, or can occur in gusts and ripples. To withstand such loading, structures require both static and dynamic strength and resilience.

Conventional windows for commercial and residential buildings generally have not been designed to withstand and/or resist the extremes of weather conditions. When subjected to high winds and debris, windows have failed or blown out, allowing weather and debris to invade the building, potentially resulting in structural damage due to the breach of structural integrity.

There therefore exists a need for an improved window construction that better resists the potential for window failure in the event of extreme weather, but that does not interfere with the normal operation of the window. Preferably such improved window construction will be readily manufactured without an undue increase in the cost of manufacture.

#### SUMMARY OF THE INVENTION

The present invention addresses these needs.

One embodiment of the present invention provides a window assembly including a window frame having a pair of frame side portions connected to a pair of frame end portions, and at least one sash having a sash frame including a pair of end rails and a pair of side rails interconnecting the end rails. The sash is movable in a plane within the window frame between a closed position in which one of its end rails is adjacent one of the frame end portions, and an open position in which the one end rail is spaced from the one frame end portion. A first member having an inner surface facing in a first direction transverse to the plane projects from the one frame end portion toward the one end rail. A second member having an outer surface facing in a direction opposite the first direction projects from the one end rail toward the one frame end portion. In the closed position of the sash, the first and second members are positioned adjacent one another with the inner surface of the first member confronting the outer surface of the second member so as to prevent movement of the sash in the second direction.

The first member may consist of a rib projecting from the frame end portion continuously from one frame side portion to the other frame side portion. Alternatively, the first member may consist of a plurality of structures projecting at spaced intervals from the frame end portion. Similarly, the second member

may consist of a rib projecting from the end rail continuously from one side rail to the other side rail, or of a plurality of structures projecting at spaced intervals from the end rail. Where both the first member  
5 and the second member include structures arranged at spaced intervals, the respective spaced intervals preferably correspond to one another.

In another embodiment of the present invention, a projecting member may project from the one frame end  
10 portion toward the one end rail, and a recess may be formed in the one end rail and be sized and shaped for receiving the projecting member in the closed position of the sash. Alternatively, the projecting member may project from the one end rail toward the one frame end  
15 portion, and the recess may be formed in the one frame end portion and be sized and shaped for receiving the projecting member in the closed position of the sash.

The projecting member may consist of a continuous rib or of a plurality of structures projecting  
20 at spaced intervals from one another. The recess also may be in the form of a continuous channel or, where the projecting member consists of a plurality of spaced projecting structures, the recess may consist of a plurality of recessed portions spaced from one another at  
25 intervals corresponding to the intervals between the projecting structures, with each recessed portion being sized and shaped for receiving a corresponding projecting structure in the closed position of the window.

#### BRIEF DESCRIPTION OF THE DRAWINGS

30 A more complete appreciation of the subject matter of the present invention and the various advantages thereof can be realized by reference to the following detailed description in which reference is made to the accompanying drawings in which:

35 Figure 1 is a front elevational view of a window assembly in accordance with the present invention;

Figure 2 is a schematic side cross-sectional view of the window assembly of Figure 1 in the closed position;

Figure 3 is a schematic side cross-sectional view of the window assembly of Figure 1 in the open position; and

Figure 4 is a schematic partial side cross-sectional view of an alternate embodiment of a window assembly in accordance with the present invention in the closed position.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is described in the following in connection with window assemblies of the type commonly used in residential buildings. Such assemblies generally include either one sash or a pair of sashes which are slidable vertically from a closed position to an open position to create an opening between the interior and exterior of the building. It will be appreciated, however, that the present invention is not limited to such window assemblies, but may also be used in connection with windows having horizontally slidable components, skylights which may be slidably opened, sliding doors and the like.

A window assembly 10 in accordance with the present invention is shown in Figure 1. The various components of window assembly 10 (other than the transparent window panels and hardware) may be made from wood, aluminum, polymers, polymer-clad wood, or other materials having structural strength and resistance to environmental exposure. In a preferred arrangement, the components of window assembly 10 may be formed from extruded polyvinyl chloride.

Referring to Figure 1, window assembly 10 includes a frame 12 having a pair of side or jamb members 14 and 16 connected at one end to a head member 18 and at an opposite end to a sill member 20. Frame 12 is

subdivided horizontally by a meeting rail 22 (Figure 2) fixedly connected between jamb members 14 and 16. A flange 24 may project outwardly along the perimeter of frame 12 for securing the window assembly to a building or other structure.

Mounted within frame 12 are two glass units, a fixed upper unit 28 and a lower unit or sash 32 which is slidable within channels (not shown) in jamb members 14 and 16 of frame 12 (upper and lower being relative to the positions shown in Figure 1). Upper unit 28 includes a panel of glazing 30 held in place between jamb members 14 and 16, head member 18 and meeting rail 22. Sash 32 includes a panel of glazing 34 held within a sash frame 36 defined by spaced side rails or stiles 21 and 23, a top rail 50 and a bottom rail 52. Glazings 30 and 34 may consist of any transparent or translucent panel, typically formed from glass or plaster, which allows light to pass therethrough. Glazings 30 and 34 may be formed from a single panel or from two or more panels assembled to form an insulating space therebetween.

Glazing 34 is mounted within sash 32 so as to be movably carried by sash frame 36 between open and closed positions of window assembly 10. In that regard, bottom rail 52 may include a lip 54 projecting toward the interior of the building to serve as an operating handle for raising and lowering sash 32. A pivotable latch 56 on top rail 50 may cooperate with a mating element 58 on meeting rail 22 to lock sash 32 in the closed position, as is well known in the art. A flexible strip 40 may be provided along the bottom edge of bottom rail 52 to produce a seal to prevent air and water from infiltrating between the bottom rail and sill member 20 of frame 12 in the closed position of sash 32.

Optionally, upper unit 28 and sash 32 each may include an artificial muntin 38 to create in the glazing the appearance of individual glass panes. Where the

glazing consists of a single glass panel, muntins 38 would ordinarily be assembled on the outdoor side thereof. Where the glazing consists of a pair of glass panels separated by an insulating space, muntins 38 may  
5 be assembled in the space between the panels.

The general arrangement of a fixed upper unit 28 and a movable sash 32 is referred to in the window art as a single hung window. A double hung window includes movable upper and lower sashes. The window assembly  
10 of the present invention may also be double hung, a single hung arrangement being shown for exemplary purposes only and not by way of limitation.

Sash 32 may be mounted to frame 12 so as to be pivotable about an axis extending parallel to top rail 50  
15 and bottom rail 52 in order to make the normally exterior side of the sash accessible for cleaning and maintenance from the interior side of the window. In accordance with such feature, which is generally known in the art, each stile of sash 32 near the bottom end thereof may include  
20 a sash guide/pivot pin apparatus (not shown) that cooperates with a sash balance assembly (not shown) slidably assembled in jamb members 14 and 16. Similarly, each stile of sash 32 near the top end thereof may include a retractable sash guide and tilt release  
25 structure (not shown) which engages within the channels in jamb members 14 and 16. Retraction of the sash guide and tilt release structures towards the center of top rail 50 releases them from the frame channels, allowing  
30 the top of sash 32 to pivot inwardly (the outward-to-inward direction being right to left in Figure 2) about the sash guide/pivot pin apparatus at the bottom of the sash. In a double-hung window arrangement, both sashes may be pivotable for convenient cleaning and maintenance. This feature is well known in the art and may be  
35 incorporated along with the storm-resistant features of the present invention.

Figure 2 is a side cross-sectional view through window assembly 10 and shows that movable sash 32 moves in a vertical plane spaced inwardly relative to a plane extending through fixed upper unit 28.

5           The blowout prevention feature of the present invention may be found in the provision of a rib 60 projecting downwardly along the length of bottom rail 52 of sash 32. With window assembly 10 in the closed position, rib 60 cooperates with a rib 62 projecting  
10           upwardly along the length of sill member 20 to prevent the blowout of sash 32. Thus, as shown in Figure 2, in the closed position of sash 32, rib 60 lies adjacent the side of rib 62 facing the interior of the building. Therefore, upon the exertion of a force tending to pull  
15           sash 32 outwardly, rib 60 will contact rib 62, preventing the bottom of sash 32 from moving transversely to its sliding plane in a direction away from the interior of the building. It will be appreciated, of course, that meeting rail 22, being fixedly secured to frame 12, will  
20           prevent top rail 50 of sash 32 from moving outwardly in the same transverse direction.

          Ribs 60 and 62 need not extend continuously along the entire lengths of bottom rail 52 and sill member 20, respectively, in order to accomplish their  
25           blowout prevention function. Thus, rib 60 may be continuous and rib 62 may be in the form of a plurality of rib segments or other structures projecting upwardly at intervals along the length of sill member 20 between jamb members 14 and 16. Alternatively, rib 62 may be  
30           continuous and rib 60 may be in the form of a plurality of rib segments or other structures projecting downwardly at intervals along the length of bottom rail 52 between stiles 21 and 23. In a still further embodiment, both rib 60 and rib 62 may be in the form of a plurality of  
35           discrete rib segments or other structures which are positioned at corresponding locations along the length of



bottom rail 52 and sill member 20, respectively, such that these structures may cooperate with one another to prevent sash 32 from blowing outwardly during extreme weather conditions.

5           Figure 3 is a side cross-sectional view through window assembly 10 with sash 32 in an open position. As can be seen, when sash 32 is raised vertically away from sill member 20 to an open position, rib 60 no longer lies adjacent to rib 62 and the blowout prevention feature of the present invention is inoperative. Accordingly, sash  
10       32 must be in the closed position shown in Figure 2, or substantially in the closed position, in order for the blowout prevention feature of the present invention to operate.

15           Although the blowout prevention feature of the present invention has been described above in connection with a single-hung window having a fixed upper glass unit and a movable lower sash, it will be appreciated that the invention can readily be incorporated in single-hung  
20       windows having a fixed lower glass unit and a movable upper sash. In such embodiments, the top rail of the movable sash would have a continuous rib or a plurality of rib segments or other structures projecting upwardly therefrom, and head member 18 of frame 12 would have a  
25       continuous rib or a plurality of rib segments or other structures projecting downwardly at intervals along the length thereof so as to lie outwardly adjacent the rib projecting from the top rail of the movable sash. In the  
30       closed position of the movable sash, the arrangement of these ribs adjacent to one another would prevent the movable sash from blowing outwardly as a result of extreme weather conditions. Of course, in double-hung windows having movable upper and lower sashes, the blowout prevention features of the present invention may  
35       be incorporated in both the lower movable sash and the upper movable sash.

Figure 4 illustrates an alternate embodiment of the blowout prevention feature in accordance with the present invention. In this embodiment, rather than having an upwardly projecting rib 62, sill member 20 includes a channel 72 formed along its length. Channel 72 is sized to receive a rib 70 projecting downwardly along the length of bottom rail 52. Rib 70 is similar to rib 60 described above, but projects a greater distance from the bottom of bottom rail 52 so as to lie within channel 72 when sash 32 is in the closed position. As with the embodiment of Figure 3, channel 72 may extend continuously along the length of sill member 20 and rib 70 may extend continuously along the length of bottom rail 52. Alternatively, channel 72 may extend continuously along the length of sill member 20 and rib 70 may be in the form of a plurality of rib segments or other structures projecting downwardly at intervals along the length of bottom rail 52 between stiles 21 and 23. In yet another arrangement, rib 70 may be in the form of a plurality of rib segments or other structures projecting downwardly at intervals along the length of bottom rail 52, and channel 72 may be in the form of a plurality of channel segments or recesses formed at corresponding intervals along the length of sill member 20. The plurality of downwardly projecting structures 70 would engage within the corresponding channel segments or recesses 72 when sash 32 is in the closed position, thereby preventing the sash from blowing outwardly in extreme weather conditions. In still further embodiments, the positions of rib or rib segments 70 and channel or channel segments 72 may be reversed, with the rib or rib segments 70 extending along the length of sill member 20 and the channel or channel segments 72 extending along the bottom of bottom rail 52. It will be appreciated, of course, that the foregoing embodiments incorporating a continuous channel or a plurality of

channel segments 72 may be used in other window assemblies, including window assemblies having a movable upper sash and double-hung window assemblies having movable upper and lower sashes.

5           Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present invention. It is therefore to be understood that  
10 numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims.

I CLAIM:

1. A window assembly, comprising  
a window frame including a pair of frame  
side portions connected to a pair of frame end portions;  
5 at least one sash having a sash frame  
including a pair of end rails and a pair of side rails  
interconnecting said end rails, said at least one sash  
being movable in a plane within said window frame between  
a closed position in which one of said end rails is  
10 adjacent one of said frame end portions, and an open  
position in which said one of said end rails is spaced  
from said one of said frame end portions;  
a first member projecting from said one of  
said frame end portions toward said one of said end  
15 rails, said first member having an inner surface facing  
in a first direction transverse to said plane;  
a second member projecting from said one  
of said end rails toward said one of said frame end  
portions, said second member having an outer surface  
20 facing in a second direction opposite said first  
direction;  
said first and second members being  
positioned adjacent one another in said closed position  
of said at least one sash with said inner surface of said  
25 first member confronting said outer surface of said  
second member so as to prevent movement of said at least  
one sash in said second direction.
2. The window assembly as claimed in claim 1,  
wherein said first member comprises a rib projecting from  
30 said one of said frame end portions.
3. The window assembly as claimed in claim 2,  
wherein said rib projects from said one of said frame end  
portions continuously from one of said frame side  
portions to the other one of said frame side portions.
- 35 4. The window assembly as claimed in claim 3,  
wherein said second member comprises a plurality of

structures projecting at spaced intervals from said one of said end rails.

5        5. The window assembly as claimed in claim 3, wherein said second member comprises a rib projecting from said one of said end rails continuously from one of said side rails to the other one of said side rails.

10       6. The window assembly as claimed in claim 1, wherein said first member comprises a plurality of structures projecting at spaced intervals from said one of said frame end portions.

7. The window assembly as claimed in claim 1, wherein said second member comprises a rib projecting from said one of said end rails.

15       8. The window assembly as claimed in claim 7, wherein said rib projects from said one of said end rails continuously from one of said side rails to the other one of said side rails.

20       9. The window assembly as claimed in claim 8, wherein said first member comprises a plurality of structures projecting at spaced intervals from said one of said frame end portions.

25       10. The window assembly as claimed in claim 1, wherein said second member comprises a plurality of structures projecting at first spaced intervals from said one of said end rails.

30       11. The window assembly as claimed in claim 10, wherein said first member comprises a plurality of structures projecting at second spaced intervals from said one of said frame end portions, said second spaced intervals corresponding to said first spaced intervals.

35       ~~12.~~ A window assembly, comprising  
             a window frame including a pair of frame side portions connected to a pair of frame end portions;  
             at least one sash having a sash frame  
             including a pair of end rails and a pair of side rails  
             interconnecting said end rails, said at least one sash

being movable in a plane within said window frame between a closed position in which one of said end rails is adjacent one of said frame end portions, and an open position in which said one of said end rails is spaced  
5 from said one of said frame end portions;

a projecting member projecting from said one of said frame end portions toward said one of said end rails; and

a recess formed in said one of said end  
10 rails and being sized and shaped for receiving said projecting member in said closed position of said at least one sash.

13. The window assembly as claimed in claim 12, wherein said projecting member comprises a rib  
15 projecting from said one of said frame end portions.

14. The window assembly as claimed in claim 13, wherein said rib projects from said one of said frame end portions continuously from one of said frame side portions to the other one of said frame side portions.

15. The window assembly as claimed in claim 14, wherein said recess comprises a channel extending continuously in said one of said end rails from one of said side rails to the other one of said side rails.  
20

16. The window assembly as claimed in claim 12, wherein said projecting member comprises a plurality of structures projecting at spaced intervals from said one of said frame end portions.  
25

17. The window assembly as claimed in claim 16, wherein said recess comprises a channel extending continuously in said one of said end rails from one of said side rails to the other one of side rails.  
30

18. The window assembly as claimed in claim 12, wherein said projecting member comprises a plurality of structures projecting at first spaced intervals from said one of said frame end portions, and said recess comprises a plurality of recessed portions formed at  
35

second spaced intervals in said one of said end rails, said second spaced intervals corresponding to said first spaced intervals, each one of said plurality of recessed portions being sized and shaped for receiving a corresponding one of said plurality of projecting structures in said closed position of said at least one sash.

19. A window assembly, comprising  
a window frame including a pair of frame side portions connected to a pair of frame end portions;  
at least one sash having a sash frame including a pair of end rails and a pair of side rails interconnecting said end rails, said at least one sash being movable in a plane within said window frame between a closed position in which one of said end rails is adjacent one of said frame end portions, and an open position in which said one of said end rails is spaced from said one of said frame end portions;

a projecting member projecting from said one of said end rails toward said one of said frame end portions; and

a recess formed in said one of said frame end portions and being sized and shaped for receiving said projecting member in said closed position of said at least one sash.

20. The window assembly as claimed in claim 19, wherein said projecting member comprises a rib projecting from said one of said end rails.

21. The window assembly as claimed in claim 20, wherein said rib projects from said one of said end rails continuously from one of said side rails to the other one of said side rails.

22. The window assembly as claimed in claim 21, wherein said recess comprises a channel extending continuously in said one of said frame end portions from

one of said frame side portions to the other one of said frame side portions.

23. The window assembly as claimed in claim 19, wherein said projecting member comprises a plurality of structures projecting at spaced intervals from said one of said end rails.

24. The window assembly as claimed in claim 23, wherein said recess comprises a channel extending continuously in said one of said frame end portions from one of said frame side portions to the other one of said frame side portions.

25. The window assembly as claimed in claim 19, wherein said projecting member comprises a plurality of structures projecting at first spaced intervals from said one of said end rails, and said recess comprises a plurality of recessed portions formed at second spaced intervals in said one of said frame end portions, said second spaced intervals corresponding to said first spaced intervals, each one of said plurality of recessed portions being sized and shaped for receiving a corresponding one of said plurality of projecting structures in said closed position of said at least one sash.




ABSTRACT OF THE DISCLOSURE

5 A storm-resistant window includes a mechanism  
for preventing the blowout of a movable sash when wind  
pressure pulls the sash outwardly. In a single hung  
10 window having a slidable lower sash, the mechanism  
consists of a first rib projecting downwardly from the  
bottom rail of the lower sash and a second rib projecting  
upwardly from the top of the sill member of the window  
frame. In a closed position of the window, the first rib  
15 lies inwardly adjacent the second rib such that, if wind  
pressure pulls the movable sash outwardly, the first rib  
will contact the second rib, preventing the bottom rail  
of the movable sash from moving outwardly. In an  
alternate embodiment, one of the ribs may be replaced  
20 with a channel, so that the remaining rib is received in  
the channel in the closed position of the window.

177279\_1.DOC

FIG. 1






FIG. 2

3/4





FIG. 3

664050-9264050

FIG. 4



# DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION

ATTORNEY'S DOCKET NO.: SILVERLINE 3.0-003

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**BLOW-OUT PREVENTION MECHANISM FOR WINDOWS** the specification of which

☒ is attached hereto  
☐ was filed on \_\_\_\_\_ as United States Application Number or PCT International Application Number \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) of any foreign application(s) for patent or inventor's certificate or § 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate, or any PCT international application having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (month, day, year)	PRIORITY CLAIMED
			YES <input type="checkbox"/> NO <input type="checkbox"/>
			YES <input type="checkbox"/> NO <input type="checkbox"/>
			YES <input type="checkbox"/> NO <input type="checkbox"/>

LISTING OF FOREIGN APPLICATIONS CONTINUED ON PAGE 3 HEREOF ☐ YES ☒ NO

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

Application Number:

Filing Date:

Application Number:

Filing Date:

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

U.S. Parent Application Serial Number:

Parent Filing Date:

Parent Patent No.:

U.S. Parent Application Serial Number:

Parent Filing Date:

Parent Patent No.:

PCT Parent Number:

Parent Filing Date:

LISTING OF US APPLICATIONS CONTINUED ON PAGE 3 HEREOF: ☐ YES ☒ NO

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

Lawrence I. Lerner, Reg. No. 19,516; Sidney David, Reg. No. 22,768; Joseph S. Littenberg, Reg. No. 20,832; Arnold H. Krumholz, Reg. No. 25,428; William L. Mentlik, Reg. No. 27,108; John R. Nelson, Reg. No. 26,573; Roy H. Wepner, Reg. No. 28,350; Stephen B. Goldman, Reg. No. 28,512; Paul H. Kochanski, Reg. No. 29,660; Marcus J. Millet, Reg. No. 28,241; Bruce H. Sales, Reg. No. 32,793; Daniel H. Bobis, Reg. No. 16,694; Keith E. Gilman, Reg. No. 32,137; Robert B. Cohen, Reg. No. 32,768; Arnold B. Dompier, Reg. No. 29,736; Michael H. Teschner, Reg. No. 32,862; Gregory S. Gewirtz, Reg. No. 36,522; Jonathan A. David, Reg. No. 36,494; Shawn P. Foley, Reg. No. 33,071; Thomas M. Palisi, Reg. No. 36,629; John P. Maldjian, Reg. No. 41,967; Kimberly V. Flügger, Reg. No. 43,612; Jason I. Garbell, Reg. No. 44,116; Renee M. Robeson, Reg. No. 41,777; Raymond W. Augustin, Reg. No. 28,588; Harvey L. Cohen, Reg. No. 28,365.

**SEND CORRESPONDENCE TO:**  
LERNER, DAVID, LITTENBERG,  
KRUMHOLZ & MENTLIK, LLP  
600 South Avenue West  
Westfield, New Jersey 07090

**DIRECT TELEPHONE CALLS TO:**  
(name and telephone number)

ROBERT B. COHEN  
(908) 654-5000 Fax: (908) 654-7866

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor (given name, family name): Arthur Silverman

Inventor's signature

*Arthur Silverman*

Date

5/3/99

Residence: 22 Rockage Road, Warren, NJ 07059 Citizenship: U.S.A.

Post Office Address: 22 Rockage Road, Warren, NJ 07059

Full name of second joint inventor, if any (given name, family name)

Second Inventor's signature

Date

Residence: Citizenship:

Post Office Address:

Full name of third joint inventor, if any (given name, family name):

Third Inventor's signature

Date

Residence: Citizenship:

Post Office Address:

Full name of fourth joint inventor, if any (given name, family name):

Fourth Inventor's signature

Date

Residence: Citizenship:

Post Office Address:

Full name of fifth joint inventor (given name, family name):

Fifth Inventor's signature

Date

Residence: Citizenship:

Post Office Address:

Full name of sixth joint inventor, if any (given name, family name):

Sixth Inventor's signature

Date

Residence: Citizenship:

Post Office Address:

Full name of seventh joint inventor, if any (given name, family name):

Seventh Inventor's signature

Date

Residence: Citizenship:

Post Office Address:

Full name of eighth joint inventor, if any (given name, family name):

Eighth Inventor's signature

Date

Residence: Citizenship:

Post Office Address:

☐ Additional inventors are being named on separately numbered sheets attached hereto.